

Electric Drum Lifter & Rotator

OVERVIEW

Optimum's battery powered bin lifters are the perfect choice for transporting, positioning, stacking or tipping loads safely and efficiently. Suitable for 55 gallon, 208 litre, steel & plastic drums, this safety conscious self-propelled drum stacker, allows you to move drums on and off racks, pallets, trucks. Ideal for stacking in horizontal position, or use for tipping of liquids.

These are lightweight and highly manoeuvrable units that have been well proven in the food, wine and meat processing industry. Optional Scales - Accumulation and Tare and Manual rotation available.

- ✓ Mild steel powder coated lift trolley
- ✓ Suitable for 55 gallon, 208 litre steel or plastic drum
- ✓ High quality hydraulic power unit
- ✓ Maintenance free 120Ah, 12V Battery
- ✓ Pump Unit Power 1.6kw
- ✓ Turning radius 1620mm
- ✓ 12 month warranty



Model DRL25

Model	Capacity	Lift Height	Lift Speed	Front Leg outer width
DRL25	520kg	1500	120mm/second	800mm

Electric Lift Platform

OVERVIEW

The Optimum Electric Lift Platform suits a wide variety of applications. The highly maneuverable, lightweight lifts are designed to take the strain out of any lifting job from ground level to over shoulder height. Idea for use in narrow aisles and confined spaces.

Perfect for all applications from pharmaceutical to catering, from packing line to food processing, from warehouse to office, kitchens, laboratories, retail outlets.

- ✓ Soft start stop
- ✓ Strong frame and steel mast design
- ✓ Fully protected & maintenance free 24V, 17Ah battery
- ✓ Load Wheel 75mm dia
- ✓ Steering Wheel 125mm dia
- ✓ 12 month warranty



Model ELP25

Model	Capacity	Lift Height	Table Size	Width	Length	Overall Height
ELP25	250kg	1700mm	470x600mm	600mm	900mm	2300mm

Fork Stackers

Optimums light weight fork stackers are a simple, economical solution for loads up to 400kg where occasional lifting is required. This sturdy lifter is a great unit to have around any workplace is extremely simple to operate. Commonly used to elevate parts, products and small skids, both manual and electric available. Comes with a removeable platform for the forks, to increase versatility.

The Optimum Bread Crate Stacker provides a unique solution for handling and stacking plastic bread crates. The battery hydraulic system will lift stacks of crates up to 250kg. The electrically operated arms grip the sides of the crates and can be clamped or released at any height, up to 1500mm.



Model BCS250

Model FS415

Model FSE415

General Trolleys

OVERVIEW

Optimum Handling Solution carry a large range of general and industrial trolleys. Optimum's high quality plastic tub trolleys are ideal for picking and packing and moving any loose items around your site. The range of stainless steel general trolleys are designed to provide a high quality, hygienic solution for the catering and food industry. The durable, plastic tray trolleys are suitable for a variety of industries, including automotive, industrial and retail applications.

Model	Capacity	Dimensions	Trolley Height	Castor Size
MLT340	340L	750x1050	840	125
MLT450	450L	730x1280	840	125
MLT650	760L	930x1530	840	125
TCT402		850x500	1050	125
TCT402SS		850x500	1050	125
TCT403		850x500	1050	125
TCT402SS		850x500	1050	125
PTT802	200kg	850x480	950	100
PTT803	200kg	850x480	1000	100
PTT1102	200kg	1100x520	950	100
PTT1103	200kg	1100x520	1000	100



Pallet Trucks

OVERVIEW

The Optimum Standard Hand Pallet Trucks are made from high quality and heavy duty steel. The benefit of having Heavy duty tandem rollers is longer lasting and easy manoeuvrability which tops the market range.

Our collection of Pallet Trucks have a durable frame design creating greater strength, vary in weight capacity and features. Carrying capacity up to 2500kg. Each one of these have a durable frame design creating greater strength. The range includes standard, narrow, gal, stainless steel and quicklift.



Model	Capacity	Max. Fork Height	Min. Fork Height	Fork Length	Overall Fork Width
PT2568	2500kg	195	85	1220	685
PT2555	2500kg	195	85	1100	550
PTG2069	2000kg	190	85	1220	685
PTSS2069	2000kg	190	85	1150	690
PTQ2068	2000kg	200	85	1150	685

